

APPARATUS FOR DETECTING A VEHICLE ROLLOVER

Background Field of the Invention

The invention proceeds from an apparatus for detecting a vehicle rollover ~~according to the species defined in the~~
independent claim.

Background Information

~~It is already known from Unexamined Application German patent~~
~~document DE 199 10 596 A1 to trigger~~ describes triggering
restraint means as a function of vehicle dynamics data. Such
data from, in particular e.g., an ESP system can be used.

~~Previously unpublished German Patent Application document DE~~
101 49 112 discloses a method for determining a triggering
decision for restraint means in a vehicle, which method makes
a triggering decision as a function of a float angle, a
transverse vehicle velocity, and the vehicle tilt angle. The
maximally achievable vehicle tilt angle is characterized by
way of a transverse vehicle acceleration and/or a transverse
vehicle velocity. An occupant detection system can
additionally be used.

Advantages of the Invention Summary

The apparatus according to the present invention for detecting
a vehicle rollover ~~having the features of the independent~~
~~claim has, in contrast,~~ the advantage that because the vehicle
state is subdivided into chronologically successive phases, a
corresponding determination of the float angle for the
individual phases is possible. In other words, a separate

calculation protocol for the float angle is used for each phase. This then makes possible, in particular, a determination of the float angle in the angle range greater than 10 degrees. The lateral velocity is also determined in this context. For vehicle rollovers with high lateral acceleration it is thus possible, in interaction with the rollover sensor suite (rotation rate about the longitudinal axis ω_x , transverse vehicle acceleration a_y , and optionally vertical vehicle acceleration a_z), to arrive at a reliable triggering decision ~~already~~ at very small roll angles, thus allowing considerably improved occupant protection as compared with conventional systems. The reason for this is that the lateral velocity, and therefore implicitly the float angle, decisively influences the rollover in the event of a soil trip. The float angle and the lateral velocity ~~are to~~ may be determined ~~hereinafter~~ by multi-stage logic. A variety of calculation methods are combined for this purpose, and an implementation of the selection of the respective method is described. The ~~assemblage is~~ method may be characterized by a sensing of the longitudinal velocity, the yaw rate (i.e. the rotation rate about the vertical axis of the vehicle), the lateral acceleration, and optionally the wheel rotation speeds, the longitudinal acceleration, and the steering angle, and an estimate of the float angle.

The operating state of a vehicle can be divided, for purposes of ~~this Application~~ the present invention, into three categories that a vehicle passes through successively in the context of a skid. These are therefore chronologically successive phases. A change from an advanced phase back into a previous state can, however, also occur. These are ~~in this case, in particular, e.g.,~~ the stable operating state, a skidding motion (which can also be referred to as the breakaway state), and the skid or skid state itself.

~~Further advantageous embodiments of the apparatus according to~~

~~the present invention are set forth in the dependent claims.~~

It is advantageous ~~in particular~~ that the stable operating state is characterized by a small and (for purposes of rollover detection) almost constant float angle, the skidding motion by a large change in float angle, and the skid by a float angle that exceeds a predefined threshold value. This allows ~~these~~ the phases to be identified in order to select the corresponding calculation protocol for the float angle.

As discussed above, it is possible for the sensor suite not only to determine measured and estimated or calculated vehicle dynamics data such as longitudinal vehicle velocity, yaw rate, and a transverse vehicle acceleration, but also to evaluate further calculated or measured variables such as wheel rotation speeds, acceleration in the longitudinal vehicle direction, steering angle, and a float angle that has been ascertained, for example, by way of a control unit for the vehicle dynamics control system. In present-day systems for vehicle dynamics control, however, the latter value has validity only for small float angles, since the vehicle state can be successfully influenced only for float angles of a few degrees, and only that range must therefore be acted upon. A device for measuring the float angle and/or the transverse vehicle velocity can also be used.

Lastly, it is also advantageous that the apparatus according to the present invention is connectable to a restraint system that activates the processor of the apparatus as a function of detection of a rollover. The result, in particular, is that according to the present invention the triggering of such restraint means, by utilization ~~according to the present invention~~ of the float angle β and lateral vehicle acceleration velocity ~~vy~~ V_y in addition to the rollover sensor suite (ω_x , a_y and a_z), becomes more accurate and more situationally appropriate.

Drawings

~~Exemplary embodiments of the invention are depicted in the drawings and will be explained in more detail in the description below.~~

~~In the drawings:~~ Brief Description of the Drawings

Figure 1 is a block diagram of the apparatus according to the present invention₁.

Figure 2 is a flow chart of the sequence executed by the apparatus according to the present invention₁.

Figure 3 is a state diagram for the sequence of the apparatus according to the present invention₁.

Figure 4 is a block diagram indicating the parameters characteristic of the stable operating state₁.

Figure 5 is a second block diagram characterizing the stable operating state₁.

Figure 6 is a first block diagram characterizing the breakaway state₁.

Figure 7 is a second block diagram characterizing the breakaway state₁.

Figure 8 is a first block diagram characterizing the skid state₁ and₁.

Figure 9 is a second block diagram characterizing the skid state.

~~Description~~ Detailed Description

Modern vehicles are equipped with restraint means, for example a window airbag or belt tensioner, that allows the occupants to be protected in the event of a vehicle rollover. Existing systems for rollover detection consider the roll motion and the accelerations in the X, Y, and Z directions of the vehicle. Reliable detection of a vehicle rollover is possible on this basis. The decision cannot be made, however, until a late point in time during the rollover, typically at a roll angle of 20 to 40 degrees. In certain instances of vehicle rollovers, however, (so-called "soil trips"), this is too late for sufficient protection of the occupant, since as a result of the high lateral acceleration he has already experienced a sideways displacement that greatly limits the usefulness of, for example, window airbags. As indicated in the existing art, a method is already known that makes possible a timely triggering decision in a context of high lateral acceleration by also incorporating the float angle and the lateral acceleration of the vehicle.

The present invention ~~proposes~~ provides, for determining the float angle in the angular range greater than 20 degrees and the lateral velocity that are to be used for rollover detection, an apparatus that subdivides the operating state of a vehicle into chronologically successive phases, a determination of the float angle and of the transverse vehicle velocity from the vehicle dynamics data being performed for each phase, and the type of determination of the float angle and of the transverse vehicle velocity being different in the individual phases.

The determination method, ~~i.e. e.g., for example~~ a calculation method, is precisely allocated to the respective phase and takes into account the physical circumstances of that phase. Three phases, ~~in particular~~ for example, are distinguished: the stable vehicle state; a skidding motion that is also referred to as the breakaway state; and the skid itself, i.e.,

the skid state.

The float angle and the lateral velocity v_y V_y are to be determined hereinafter by multi-stage logic. A variety of calculation methods are combined for that purpose, and an implementation of the selection of the respective method is described.

Figure 1 is a block diagram of the apparatus according to the present invention. A sensor suite 1 is connected via a data output to a processor 2. Processor 2, which also has memory means, is connected via a data output to a restraint system 3. Sensor suite 1 supplies vehicle dynamics data and rollover data (yaw rate and horizontal accelerations). Sensor suite 1 has acceleration and rotation-rate sensors for that purpose. Sensing of the wheel rotation speed and the steering angle can also be provided in sensor suite 1. Sensor suite 1 can be distributed in the vehicle and/or concentrated in a central control device. Here sensor suite 1 already supplies a digital signal to processor 2. Digital sensors that already output a digitized sensor signal are generally used.

It is possible to use analog sensors whose signal is digitized either in processor 2 or by way of a separate analog/digital converter. Digitization is necessary for further processing. Sensor suite 1 can also encompass a control unit for vehicle dynamics control that can indicate an estimated value for a float angle at small angles. Such vehicle dynamics control systems are, ~~as a rule~~ generally suitable only for angle ranges below 10 degrees, for example, methods that use a model made up of tire characteristics and lateral guidance force. Vehicle dynamics control may no longer be performed successfully, in particular, at greater float angles. Sensor suite 1 can likewise have a control unit that supplies calculated or prepared variables, for example, the longitudinal vehicle velocity.

Sensor suite 1 can therefore, as indicated above, be disposed outside a housing in which processor 2 is located. The electrical connection between sensor suite 1 and processor 2 can be implemented by way of a bus or a two-wire conductor or a plurality of two-wire conductors. In the case of two-wire conductors ~~in particular~~, it is possible for the information flow to be established unidirectionally from sensor suite 1 to processor 2.

In addition to the conventional rollover sensor suite (ω_x , a_y , and a_z), processor 2 evaluates the vehicle dynamics data of sensor suite 1 and can detect a vehicle rollover therefrom by ascertaining the float angle and the transverse vehicle velocity. The float angle and the transverse vehicle acceleration are now determined here as a function of the identified phase of the operating state. A separate calculation protocol is provided for each phase. Here, ~~in particular~~, three phases ~~are~~ may be provided: the stable operating state, a breakaway state, and the skid state. A subdivision into more or fewer than three phases is, ~~in principle~~, also possible.

The vehicle is initially in the stable operating state, which includes cornering at a low float angle. When this state exists, the float angle and the lateral velocity are of no interest for rollover detection because they are too low to initiate a rollover motion. The value resulting as an estimated lateral velocity v_{y0} is therefore zero. In this phase, the estimated float angle β_0 can be regarded as a constant for rollover detection, the constant being vehicle-dependent and being determined by way of the maximum achievable float angle during cornering. As ~~a variant~~ an alternative, it is also possible to use the float angle β_{ESP} , as calculated, e.g., in a control unit using tire characteristic models, as a transfer value for the next state. A further ~~variant~~ alternative is to determine the float angle

β_0 that is to be used at the transition to phase 2 by estimating the vehicle situation, for example on the basis of a steering angle (suitably filtered, if applicable), the yaw rate, and the transverse vehicle acceleration.

5

The second phase is characterized by an incipient skidding motion. This can be detected, for example, by way of a large change in float angle or a sharp drop in a lateral acceleration previously of longer duration. The basis for this is that a skid begins, inter alia, when the lateral guidance forces during cornering are no longer sufficient to keep the vehicle stable, and the wheels therefore slip laterally.

10

The change in float angle is calculated using the following equation:

15

$$\dot{\beta} = \omega_z \frac{a_y \cos^2(\beta) + a_x \cos(\beta) \sin(\beta)}{v_x} \approx \omega_z - \frac{a_y}{v_x} \text{ for small values of } \beta$$

In this phase the float angle β_1 can be determined by additively integrating the change in float angle, taking as the initial value the previously ascertained value β_0 from phase 1. This is then determined with the following equation:

20

$$\beta_1 = \beta_0 + \int \dot{\beta} dt$$

25

The lateral velocity $v_{y,1}$ is then obtained from the float angle β_1 and the vehicle's longitudinal velocity v_x :

$$v_{y,1} = v_x \tan(\beta_1).$$

30

The third phase is characterized by skidding of the vehicle. This is detectable, for example, by way of a float angle β_1

beyond a specific threshold β_{\min} and/or by locking of the wheels at a yaw rate ω_z greater than a minimum yaw rate $\omega_{z\min}$.

The float angle β_2 is then calculated by additive integration of the yaw rate, the previously ascertained value β_1 from the second phase being taken as the initial value;

$$\beta_2' = \beta_1 + \int \omega_z dt .$$

The lateral velocity is then obtained from the float angle and the center-of-mass velocity v_{sp} V_{sp} of the vehicle:

$$v_{y,2} = v_{sp} \sin(\beta_2) .$$

The center-of-mass velocity is obtained from the initial longitudinal velocity, the initial lateral velocity, and the lateral acceleration a_y , and optionally the longitudinal acceleration a_x .

Figure 2 ~~visualizes in~~ is a flow chart illustrating the sequence occurring in the apparatus according to the present invention shown in Figure 1. In method step 4, sensor suite 1 delivers the vehicle dynamics data to processor 2. Method step 5 then checks whether the stable state is being departed from, i.e. whether a breakaway situation exists. Processor 2 checks this on the basis of the vehicle dynamics data. If that is not the case, execution branches back to method step 4. If it is the case, however, the breakaway state is then detected in method step 6 and the float angle is determined as described above. This also applies to the transverse vehicle velocity. Method step 7 then checks whether phase 3, i.e., the skid state, has been reached. If that is not the case, execution branches back to method step 5. If it is the case, however, execution then branches to method step 8 and we are in the detected skid state, the float angle and transverse vehicle

velocity now being determined as indicated above. Method step 9 then checks whether a vehicle rollover has been detected on the basis of the vehicle dynamics data and the rollover sensor suite (ω_x , a_y , and a_z). If that is not the case, execution branches back to method step 5. If it is the case, however, execution then branches to method step 10, and restraint means 3 are activated by processor 2. In the context of a vehicle rollover, these are, for example, airbags that protect the head region in particular, a roll bar, and belt tensioners that prevent the person from sliding out (i.e., the "submarining" effect) during a rollover.

Figure 3 shows a diagram of the states through which the apparatus according to the present invention passes. From a stable operating state 11, the apparatus moves into breakaway state 12 when, as presented above, a breakaway detection exists. The transfer parameter that is transferred is the float angle β_0 . In breakaway state 12, a check is made as to whether a stable state is detected or a skid state exists. If a stable operating state was detected, the system then moves from breakaway state 12 back into stable operating state 11. If a skid state is detected, however, the system then moves to state 13 (the skid state), and the float angle β_1 is transferred as a parameter.

If neither of the two is present, the system remains in breakaway state 12. In the skid state, a check is then made as to whether the stable operating state again exists. In that case the system moves from state 13 back into stable operating state 11. A check is also made as to whether the restraint means are to be triggered.

Figure 4 shows that the estimated float angle value β_0 and a transverse vehicle velocity of zero are present as output parameters of the stable operating state. Figure 5 depicts a variant in which the float angle β_{ESP} is supplied by the

vehicle dynamics control system. In that case as well, the float angle β_0 and a transverse vehicle velocity v_y equal to zero are present as output values.

5 Figure 6 shows the parameters involved in determining the float angle β_1 and transverse vehicle velocity v_{y1} in the breakaway state. This requires the float angle β_0 from the stable operating state, the longitudinal vehicle velocity v_x , the yaw rate ω_z , the transverse vehicle acceleration a_y , and
10 the longitudinal vehicle acceleration a_x . As shown in Figure 7, it is also possible to omit the longitudinal vehicle acceleration and to determine the float angle β_1 and transverse vehicle velocity v_{y1} using only the float angle β_0 , longitudinal vehicle velocity v_x , yaw rate ω_z , and transverse
15 vehicle acceleration a_y .

Figure 8 shows the parameters necessary for determination of the float angle β_2 and transverse vehicle velocity v_{y2} in the skid state. Here these are the float angle β_1 , longitudinal
20 vehicle velocity v_x , yaw rate ω_z , transverse vehicle velocity v_{y1} , longitudinal vehicle acceleration a_x , and transverse vehicle acceleration a_y . As depicted in Figure 9, it is alternatively possible to omit the longitudinal vehicle acceleration.

25

Abstract

ABSTRACT

An apparatus for detecting a vehicle rollover comprising
includes a sensor suite (1) for sensing vehicle dynamics data
5 ~~is proposed~~, the sensor suite (1) being ~~connectable~~ connected
to a processor (2) which is configured in such a way that the
processor (2) detects a vehicle rollover as a function of the
vehicle dynamics data and the rollover sensor suite,
~~characterized in that the~~. The processor (2) has means for
10 dividing an operating state of the vehicle into
chronologically successive phases~~;~~. In particular, the
processor (2) ~~having, for each phase,~~ has means for
determining, for each phase, a float angle and a transverse
vehicle velocity from the vehicle dynamics data; the float
15 angle and the transverse vehicle velocity being ~~usable~~ used,
together with the data from the rollover sensor suite, for
detection of the vehicle rollover.

~~(Figure 1)~~